DESKBOUND DEVICES
PCS

Fujitsu presents a range of PCs characterized by high ergonomic standards, sophisticated product concepts and the best value. With our selection of ESPRIMO systems we have the right product to suit every customer's requirements: ranging from solid, reliable everyday use up to performance and the latest technologies for highest demands.
We offer desktop PCs that continue our 15-year record as a green innovator.



SUPERIOR PCS
ESPRIMO

Windows®. Life without Walls™.
Fujitsu recommends Windows 7.

	ESPRIMO P9900 0-WATT	ESPRIMO P9900 E-STAR 5.0
	The innovative 0-Watt PC	The expandable business workhorse
Operating system preinstalled	Genuine Windows® 7 Home Premium Genuine Windows® 7 Professional TwinLoad Windows® XP Professional (DVD)	Genuine Windows® 7 Home Premium Genuine Windows® 7 Professional TwinLoad Windows® XP Professional (DVD)
Facts Mainboard	D2912 (µBTX)	D2912 (µBTX)
Chipset	Intel® Q57	Intel® Q57
Processor Type, Second Level cache, Front side bus	Intel® Core™ i7 processor i7-860, 8 MB Intel® Core™ i5 processor i5-750, 8 MB Intel® Core™ i5 processor i5-670, 4 MB Intel® Core™ i5 processor i5-660, 4 MB Intel® Core™ i5 processor i5-650, 4 MB Intel® Core™ i3 processor i3-530, 4 MB Intel® Pentium® processor G6950, 3 MB	Intel® Core™ i7 processor i7-860, 8 MB Intel® Core™ i5 processor i5-750, 8 MB Intel® Core™ i5 processor i5-670, 4 MB Intel® Core™ i5 processor i5-660, 4 MB Intel® Core™ i5 processor i5-650, 4 MB Intel® Core™ i3 processor i3-530, 4 MB Intel® Pentium® processor G6950, 3 MB
Memory	Up to 16 GB, 4 DIMM (DDR3, 1333 MHz) slot(s) Dual channel support. For dual channel performance, identical memory modules in each channel are necessary (minimum 2 modules).	Up to 16 GB, 4 DIMM (DDR3, 1333 MHz) slot(s) Dual channel support. For dual channel performance, identical memory modules in each channel are necessary (minimum 2 modules).
Serial ATA	4	4
thereof eSATA	2 (optional)	2 (optional)
Controller functions	Serial ATA II, NCQ and 3 GBit, AHCI, Raid 1/0	Serial ATA II, NCQ and 3 GBit, AHCI, Raid 1/0
Drives (optional)	DVD-ROM, SATA I DVD Super Multi, SATA I Blu-ray Disc Triple Writer, SATA I MultiCard Reader 20in1, 3.5-inch, USB 2.0	DVD-ROM, SATA I DVD Super Multi, SATA I Blu-ray Disc Triple Writer, SATA I MultiCard Reader 20in1, 3.5-inch, USB 2.0
Hard disk drive	SATA II, 7200 rpm, 160 GB, 2.5-inch, S.M.A.R.T. SATA II, 7200 rpm, 250 GB, 3.5-inch, S.M.A.R.T. SATA II, 7200 rpm, 320 GB, 3.5-inch, S.M.A.R.T. SATA II, 7200 rpm, 500 GB, 3.5-inch, S.M.A.R.T. SATA II, 7200 rpm, 500 GB, 3.5-inch, S.M.A.R.T. business critical SATA II, 7200 rpm, 1000 GB, 3.5-inch, S.M.A.R.T. SSD SATA, 128 GB, 2.5-inch	SATA II, 7200 rpm, 160 GB, 2.5-inch, S.M.A.R.T. SATA II, 7200 rpm, 250 GB, 3.5-inch, S.M.A.R.T. SATA II, 7200 rpm, 320 GB, 3.5-inch, S.M.A.R.T. SATA II, 7200 rpm, 500 GB, 3.5-inch, S.M.A.R.T. SATA II, 7200 rpm, 500 GB, 3.5-inch, S.M.A.R.T. business critical SATA II, 7200 rpm, 1000 GB, 3.5-inch, S.M.A.R.T. SSD SATA, 128 GB, 2.5-inch
Drive bays	2 x 3.5-inch external bay; 2 x 3.5-inch internal bay; 2 x 5.25-inch external bay	2 x 3.5-inch external bay; 2 x 3.5-inch internal bay; 2 x 5.25-inch external bay
Slots	1 x PCI-Express 2.0 x16; 2 x PCI slots	1 x PCI-Express 2.0 x16; 2 x PCI slots
Interfaces	1 x Audio: line-in / microphone; 1 x Audio: line-in; 1 x Audio: line-out; 1 x Front audio: headphone; 1 x Front audio: microphone; 14 x USB 2.0 total; 2 x USB front; 8 x USB rear; 4 x USB internal; VGA via DVI to VGA adaptor (included for onboard graphics only); 1 x Serial (9pi, 16 byte FIFO, 16550 compatible) (RS-232); optional Parallel (25pin with EPP and ECP); 1 x Ethernet (RJ-45); 1 x (for onboard graphics only) DVI; 1 x (for onboard graphics only) DisplayPort; 2 x Mouse / Keyboard (PS/2)	1 x Audio: line-in / microphone; 1 x Audio: line-in; 1 x Audio: line-out; 1 x Front audio: headphone; 1 x Front audio: microphone; 14 x USB 2.0 total; 2 x USB front; 8 x USB rear; 4 x USB internal; VGA via DVI to VGA adaptor (included for onboard graphics only); 1 x Serial (9pi, 16 byte FIFO, 16550 compatible) (RS-232); optional Parallel (25pin with EPP and ECP); 1 x Ethernet (RJ-45); 1 x (for onboard graphics only) DVI; 1 x (for onboard graphics only) DisplayPort; 2 x Mouse / Keyboard (PS/2)
Graphics	Up to 1759 MB Graphics controller integrated in dual-core processor. For quad-core processors graphics card is mandatory	Up to 1759 MB Graphics controller integrated in dual-core processor. For quad-core processors graphics card is mandatory
Audio codec	Realtek ALC663	Realtek ALC663
LAN	10/100/1000 MBit/s Intel® 82567 LM	10/100/1000 MBit/s Intel® 82567 LM
Dimensions (W x D x H)	203 x 390 x 392 mm	203 x 390 x 392 mm
Power efficiency	Power supply efficiency (at 230V; 20% / 50% / 100% load): 86% / 89% / 87%	Power supply efficiency (at 230V; 20% / 50% / 100% load): 85% / 87% / 85%
Special features	0-Watt in off- / hibernating mode, Intel® vPro™ technology, Green PC, ENERGY STAR® 5.0, 89% energy efficient power supply, Blue Angel certified, Switched monitor outlet, Family Concept, Twinload, Embedded Security (TPM)	Intel® vPro™ technology, Green PC, ENERGY STAR® 5.0, up to 87% energy efficient power supply, Blue Angel certified, Family Concept, Twinload
Standard Warranty Duration	3 years	3 years
Service Level*	Bring-In/On-Site Service (depending on country)	Bring-In/On-Site Service (depending on country)

SUPERIOR PCS
ESPRIMO

Windows®. Life without Walls™.
Fujitsu recommends Windows 7.

	ESPRIMO E9900 0-WATT	ESPRIMO E9900 E-STAR 5.0
	The innovative 0-Watt PC	Your desktop without compromises
Operating system preinstalled	Genuine Windows® 7 Home Premium Genuine Windows® 7 Professional TwinLoad Windows® XP Professional (DVD)	Genuine Windows® 7 Home Premium Genuine Windows® 7 Professional TwinLoad Windows® XP Professional (DVD)
Facts Mainboard	D2924 (proprietary)	D2924 (proprietary)
Chipset	Intel® Q57	Intel® Q57
Processor Type, Second Level cache, Front side bus	Intel® Core™ i7 processor i7-860, 8 MB Intel® Core™ i5 processor i5-750, 8 MB Intel® Core™ i5 processor i5-670, 4 MB Intel® Core™ i5 processor i5-660, 4 MB Intel® Core™ i5 processor i5-650, 4 MB Intel® Core™ i3 processor i3-530, 4 MB Intel® Pentium® processor G6950, 3 MB	Intel® Core™ i7 processor i7-860, 8 MB Intel® Core™ i5 processor i5-750, 8 MB Intel® Core™ i5 processor i5-670, 4 MB Intel® Core™ i5 processor i5-660, 4 MB Intel® Core™ i5 processor i5-650, 4 MB Intel® Core™ i3 processor i3-530, 4 MB Intel® Pentium® processor G6950, 3 MB
Memory	Up to 16 GB, 4 DIMM (DDR3, 1333 MHz) slot(s) Dual channel support. For dual channel performance, identical memory modules in each channel are necessary (minimum 2 modules).	Up to 16 GB, 4 DIMM (DDR3, 1333 MHz) slot(s) Dual channel support. For dual channel performance, identical memory modules in each channel are necessary (minimum 2 modules).
Serial ATA	4	4
thereof eSATA	2 (optional)	2 (optional)
Controller functions	Serial ATA II, NCQ and 3 GBit, AHCI, Raid 1/0	Serial ATA II, NCQ and 3 GBit, AHCI, Raid 1/0
Drives (optional)	DVD-ROM, SATA I DVD Super Multi, SATA I Blu-ray Disc Triple Writer, SATA I MultiCard Reader 20in1, 3.5-inch, USB 2.0	DVD-ROM, SATA I DVD Super Multi, SATA I Blu-ray Disc Triple Writer, SATA I MultiCard Reader 20in1, 3.5-inch, USB 2.0
Hard disk drive	SATA II, 7200 rpm, 160 GB, 2.5-inch, S.M.A.R.T. SATA II, 7200 rpm, 250 GB, 3.5-inch, S.M.A.R.T. SATA II, 7200 rpm, 320 GB, 3.5-inch, S.M.A.R.T. SATA II, 7200 rpm, 500 GB, 3.5-inch, S.M.A.R.T. SATA II, 7200 rpm, 500 GB, 3.5-inch, S.M.A.R.T. business critical SATA II, 7200 rpm, 1000 GB, 3.5-inch, S.M.A.R.T. SSD SATA, 128 GB, 2.5-inch	SATA II, 7200 rpm, 160 GB, 2.5-inch, S.M.A.R.T. SATA II, 7200 rpm, 250 GB, 3.5-inch, S.M.A.R.T. SATA II, 7200 rpm, 320 GB, 3.5-inch, S.M.A.R.T. SATA II, 7200 rpm, 500 GB, 3.5-inch, S.M.A.R.T. SATA II, 7200 rpm, 500 GB, 3.5-inch, S.M.A.R.T. business critical SATA II, 7200 rpm, 1000 GB, 3.5-inch, S.M.A.R.T. SSD SATA, 128 GB, 2.5-inch
Drive bays	1 x 3.5-inch external bay; 1 x 3.5-inch internal bay; 1 x 5.25-inch external bay	1 x 3.5-inch external bay; 1 x 3.5-inch internal bay; 1 x 5.25-inch external bay
Slots	1 x PCI-Express 2.0 x16; 2 x PCI slots	1 x PCI-Express 2.0 x16; 2 x PCI slots
Interfaces	1 x Audio: line-in; 1 x Audio: line-out; 1 x Front audio: headphone; 1 x Front audio: microphone; 12 x USB 2.0 total; 2 x USB front; 6 x USB rear; 4 x USB internal; VGA via DVI to VGA adaptor (included for onboard graphics only); 1 x Serial (9pin, 16 byte FIFO, 16550 compatible) (RS-232); optional Parallel (25pin with EPP and ECP); 1 x Ethernet (RJ-45); 1 x (for onboard graphics only) DVI; 1 x (for onboard graphics only) DisplayPort; 2 x Mouse / Keyboard (PS/2)	1 x Audio: line-in; 1 x Audio: line-out; 1 x Front audio: headphone; 1 x Front audio: microphone; 12 x USB 2.0 total; 2 x USB front; 6 x USB rear; 4 x USB internal; VGA via DVI to VGA adaptor (included for onboard graphics only); 1 x Serial (9pin, 16 byte FIFO, 16550 compatible) (RS-232); optional Parallel (25pin with EPP and ECP); 1 x Ethernet (RJ-45); 1 x (for onboard graphics only) DVI; 1 x (for onboard graphics only) DisplayPort; 2 x Mouse / Keyboard (PS/2)
Graphics	Up to 1759 MB Graphics controller integrated in dual-core processor. For quad-core processors graphics card is mandatory	Up to 1759 MB Graphics controller integrated in dual-core processor. For quad-core processors graphics card is mandatory
Audio codec	Realtek ALC663	Realtek ALC663
LAN	10/100/1000 MBit/s Intel® 82567 LM	10/100/1000 MBit/s Intel® 82567 LM
Dimensions (W x D x H)	340 x 380 x 100 mm	340 x 380 x 100 mm
Power efficiency	Power supply efficiency (at 230V; 20% / 50% / 100% load): 86% / 89% / 87%	Power supply efficiency (at 230V; 20% / 50% / 100% load): 84% / 87% / 85%
Special features	0-Watt in off- / hibernating mode, Intel® vPro™ technology, Green PC, ENERGY STAR® 5.0, 89% energy efficient power supply, Blue Angel certified, Switched monitor outlet, Family Concept, Twinload, Embedded Security (TPM)	Intel® vPro™ technology, Green PC, ENERGY STAR® 5.0, up to 87% energy efficient power supply, Blue Angel certified, Family Concept, Twinload
Standard Warranty Duration	3 years	3 years
Service Level*	Bring-In/On-Site Service (depending on country)	Bring-In/On-Site Service (depending on country)

SUPERIOR PCS
ESPRIMO

Windows®. Life without Walls™.
Fujitsu recommends Windows 7.

ESPRIMO P7936 0-WATT

	The world's first 0-Watt PC
Operating system preinstalled	Genuine Windows® 7 Home Premium Genuine Windows® 7 Professional TwinLoad Windows® XP Professional (DVD)
Facts Mainboard	D3012 (µBTX)
Chipset	Intel® Q45
Processor Type, Second Level cache, Front side bus	Intel® Core™2 Quad processor Q9650, 12 MB, 1333 MHz Intel® Core™2 Quad processor Q9550, 12 MB, 1333 MHz Intel® Core™2 Quad processor Q9505, 6 MB, 1333 MHz Intel® Core™2 Quad processor Q8300, 4 MB, 1333 MHz Intel® Core™2 Duo processor E8600, 6 MB, 1333 MHz Intel® Core™2 Duo processor E8500, 6 MB, 1333 MHz Intel® Core™2 Duo processor E8400, 6 MB, 1333 MHz Intel® Core™2 Duo processor E7600, 3 MB, 1066 MHz Intel® Core™2 Duo processor E7500, 3 MB, 1066 MHz Intel® Pentium® processor E6300, 2 MB, 1066 MHz Intel® Pentium® processor E5500, 2 MB, 1066 MHz Intel® Pentium® processor E5400, 2 MB, 800 MHz Intel® Celeron® processor E3200, 1 MB, 800 MHz
Memory	Up to 16 GB, 4 DIMM (DDR3, 1066 MHz) slot(s) Dual channel support. For dual channel performance, identical memory modules in each channel are necessary (minimum 2 modules).
Serial ATA	4
thereof eSATA	2 (optional)
Controller functions	Serial ATA II, NCQ and 3 GBit, AHCI, Raid 1/0
Drives (optional)	1.44 MB Floppy DVD-ROM, SATA I DVD Super Multi, SATA I Blu-ray Disc Triple Writer, SATA I MultiCard Reader 20in1, 3.5-inch, USB 2.0
Hard disk drive	SATA II, 7200 rpm, 160 GB, 2.5-inch, S.M.A.R.T. SATA II, 7200 rpm, 160 GB, 3.5-inch, S.M.A.R.T. SATA II, 7200 rpm, 250 GB, 3.5-inch, S.M.A.R.T. SATA II, 7200 rpm, 320 GB, 3.5-inch, S.M.A.R.T. SATA II, 7200 rpm, 500 GB, 3.5-inch, S.M.A.R.T. SATA II, 7200 rpm, 500 GB, 3.5-inch, S.M.A.R.T. business critical SATA II, 7200 rpm, 1000 GB, 3.5-inch, S.M.A.R.T. SSD SATA, 128 GB, 2.5-inch
Drive bays	2 x 3.5-inch external bay 2 x 3.5-inch internal bay 2 x 5.25-inch external bay
Slots	1 x PCI-Express 2.0 x16 1 x PCI-Express x4 (mech. x8) 2 x PCI slots

Interfaces	1 x Audio: line-in / microphone 1 x Audio: line-in 1 x Audio: line-out 1 x Front audio: headphone 1 x Front audio: microphone 12 x USB 2.0 total 2 x USB front 6 x USB rear 4 x USB internal, thereof 2 optional rear 1 x VGA 1 x Serial (9pin, 16 byte FIFO, 16550 compatible) (RS-232) optional Parallel (25pin with EPP and ECP) 1 x Ethernet (RJ-45) optional DVI optional DisplayPort 2 x Mouse / Keyboard (PS/2)
Graphics	Intel® GMA 4500, up to 1759 MB
Audio codec	Realtek ALC663
LAN	10/100/1000 MBit/s Intel® 82567 LM
Dimensions (W x D x H)	203 x 390 x 392 mm
Power efficiency	Power supply efficiency (at 230V; 20% / 50% / 100% load): 86% / 89% / 87%
Special features	0-Watt in off- / hibernating mode, Intel® vPro™ technology, Green PC, ENERGY STAR® 5.0, 89% energy efficient power supply, Blue Angel certified, Switched monitor outlet, Family Concept, Twinload, Embedded Security (TPM)
Standard Warranty Duration	3 years
Service Level*	Bring-In/On-Site Service (depending on country)

Windows®. Life without Walls™.
Fujitsu recommends Windows 7.

ESPRIMO P7936 E-STAR 5.0

	The expandable business workhorse
Operating system preinstalled	Genuine Windows® 7 Home Premium Genuine Windows® 7 Professional TwinLoad Windows® XP Professional (DVD)
Facts Mainboard	D3012 (µBTX)
Chipset	Intel® Q45
Processor Type, Second Level cache, Front side bus	Intel® Core™2 Quad processor Q9650, 12 MB, 1333 MHz Intel® Core™2 Quad processor Q9550, 12 MB, 1333 MHz Intel® Core™2 Quad processor Q9505, 6 MB, 1333 MHz Intel® Core™2 Quad processor Q8300, 4 MB, 1333 MHz Intel® Core™2 Duo processor E8600, 6 MB, 1333 MHz Intel® Core™2 Duo processor E8500, 6 MB, 1333 MHz Intel® Core™2 Duo processor E8400, 6 MB, 1333 MHz Intel® Core™2 Duo processor E7600, 3 MB, 1066 MHz Intel® Core™2 Duo processor E7500, 3 MB, 1066 MHz Intel® Pentium® processor E6300, 2 MB, 1066 MHz Intel® Pentium® processor E5500, 2 MB, 1066 MHz Intel® Pentium® processor E5400, 2 MB, 800 MHz Intel® Celeron® processor E3200, 1 MB, 800 MHz
Memory	Up to 16 GB, 4 DIMM (DDR3, 1066 MHz) slot(s) Dual channel support. For dual channel performance, identical memory modules in each channel are necessary (minimum 2 modules).
Serial ATA	4
thereof eSATA	2 (optional)
Controller functions	Serial ATA II, NCQ and 3 GBit, AHCI, Raid 1/0
Drives (optional)	1.44 MB Floppy DVD-ROM, SATA I DVD Super Multi, SATA I Blu-ray Disc Triple Writer, SATA I MultiCard Reader 20in1, 3.5-inch, USB 2.0
Hard disk drive	SATA II, 7200 rpm, 160 GB, 2.5-inch, S.M.A.R.T. SATA II, 7200 rpm, 160 GB, 3.5-inch, S.M.A.R.T. SATA II, 7200 rpm, 250 GB, 3.5-inch, S.M.A.R.T. SATA II, 7200 rpm, 320 GB, 3.5-inch, S.M.A.R.T. SATA II, 7200 rpm, 500 GB, 3.5-inch, S.M.A.R.T. SATA II, 7200 rpm, 500 GB, 3.5-inch, S.M.A.R.T. business critical SATA II, 7200 rpm, 1000 GB, 3.5-inch, S.M.A.R.T. SSD SATA, 128 GB, 2.5-inch
Drive bays	2 x 3.5-inch external bay 2 x 3.5-inch internal bay 2 x 5.25-inch external bay
Slots	1 x PCI-Express 2.0 x16 1 x PCI-Express x4 (mech. x8) 2 x PCI slots
Interfaces	1 x Audio: line-in / microphone 1 x Audio: line-in 1 x Audio: line-out 1 x Front audio: headphone 1 x Front audio: microphone 12 x USB 2.0 total 2 x USB front 6 x USB rear 4 x USB internal, thereof 2 optional rear 1 x VGA 1 x Serial (9pin, 16 byte FIFO, 16550 compatible) (RS-232) optional Parallel (25pin with EPP and ECP) 1 x Ethernet (RJ-45) optional DVI optional DisplayPort 2 x Mouse / Keyboard (PS/2)
Graphics	Intel® GMA 4500, up to 1759 MB
Audio codec	Realtek ALC663
LAN	10/100/1000 MBit/s Intel® 82567 LM
Dimensions (W x D x H)	203 x 390 x 392 mm
Power efficiency	Power supply efficiency (at 230V; 20% / 50% / 100% load): 85% / 87% / 85%
Special features	Intel® vPro™ technology, Green PC, ENERGY STAR® 5.0, up to 87% energy efficient power supply, Blue Angel certified, Family Concept, Twinload
Standard Warranty Duration	3 years
Service Level*	Bring-In/On-Site Service (depending on country)

Windows®. Life without Walls™.
Fujitsu recommends Windows 7.

ESPRIMO P7936 E85+

	The expandable business workhorse
Operating system preinstalled	Genuine Windows® 7 Home Premium Genuine Windows® 7 Professional TwinLoad Windows® XP Professional (DVD)
Facts Mainboard	D3012 (µBTX)
Chipset	Intel® Q45
Processor Type, Second Level cache, Front side bus	Intel® Core™2 Quad processor Q9650, 12 MB, 1333 MHz Intel® Core™2 Quad processor Q9550, 12 MB, 1333 MHz Intel® Core™2 Quad processor Q9505, 6 MB, 1333 MHz Intel® Core™2 Quad processor Q8300, 4 MB, 1333 MHz Intel® Core™2 Duo processor E8600, 6 MB, 1333 MHz Intel® Core™2 Duo processor E8500, 6 MB, 1333 MHz Intel® Core™2 Duo processor E8400, 6 MB, 1333 MHz Intel® Core™2 Duo processor E7600, 3 MB, 1066 MHz Intel® Core™2 Duo processor E7500, 3 MB, 1066 MHz Intel® Pentium® processor E6300, 2 MB, 1066 MHz Intel® Pentium® processor E5500, 2 MB, 1066 MHz Intel® Pentium® processor E5400, 2 MB, 800 MHz Intel® Celeron® processor E3200, 1 MB, 800 MHz Intel® Celeron® processor 450, 512 KB, 800 MHz
Memory	Up to 16 GB, 4 DIMM (DDR3, 1066 MHz) slot(s) Dual channel support. For dual channel performance, identical memory modules in each channel are necessary (minimum 2 modules).
Serial ATA	4
thereof eSATA	2 (optional)
Controller functions	Serial ATA II, NCQ and 3 GBit, AHCI, Raid 1/0
Drives (optional)	1.44 MB Floppy DVD-ROM, SATA I DVD Super Multi, SATA I Blu-ray Disc Triple Writer, SATA I MultiCard Reader 20in1, 3.5-inch, USB 2.0
Hard disk drive	SATA II, 7200 rpm, 160 GB, 2.5-inch, S.M.A.R.T. SATA II, 7200 rpm, 160 GB, 3.5-inch, S.M.A.R.T. SATA II, 7200 rpm, 250 GB, 3.5-inch, S.M.A.R.T. SATA II, 7200 rpm, 320 GB, 3.5-inch, S.M.A.R.T. SATA II, 7200 rpm, 500 GB, 3.5-inch, S.M.A.R.T. SATA II, 7200 rpm, 500 GB, 3.5-inch, S.M.A.R.T. business critical SATA II, 7200 rpm, 1000 GB, 3.5-inch, S.M.A.R.T. SSD SATA, 128 GB, 2.5-inch
Drive bays	2 x 3.5-inch external bay 2 x 3.5-inch internal bay 2 x 5.25-inch external bay
Slots	1 x PCI-Express 2.0 x16 1 x PCI-Express x4 (mech. x8) 2 x PCI slots
Interfaces	1 x Audio: line-in / microphone 1 x Audio: line-in 1 x Audio: line-out 1 x Front audio: headphone 1 x Front audio: microphone 12 x USB 2.0 total 2 x USB front 6 x USB rear 4 x USB internal, thereof 2 optional rear 1 x VGA 1 x Serial (9pin, 16 byte FIFO, 16550 compatible) (RS-232) optional Parallel (25pin with EPP and ECP) 1 x Ethernet (RJ-45) optional DVI optional DisplayPort 2 x Mouse / Keyboard (PS/2)
Graphics	Intel® GMA 4500, up to 1759 MB
Audio codec	Realtek ALC663
LAN	10/100/1000 MBit/s Intel® 82567 LM
Dimensions (W x D x H)	203 x 390 x 392 mm
Power efficiency	Power supply efficiency (at 230V; 20% / 50% / 100% load): 85% / 87% / 85%
Special features	Intel® vPro™ technology, Green PC, up to 87% energy efficient power supply, Blue Angel certified, Family Concept, Twinload
Standard Warranty Duration	3 years
Service Level*	Bring-In/On-Site Service (depending on country)

ESPRIMO E7936 0-WATT

	The innovative 0-Watt PC
Operating system preinstalled	Genuine Windows® 7 Home Premium Genuine Windows® 7 Professional TwinLoad Windows® XP Professional (DVD)
Facts Mainboard	D3028 (proprietary)
Chipset	Intel® Q45
Processor Type, Second Level cache, Front side bus	Intel® Core™2 Quad processor Q9650, 12 MB, 1333 MHz Intel® Core™2 Quad processor Q9550, 12 MB, 1333 MHz Intel® Core™2 Quad processor Q9505, 6 MB, 1333 MHz Intel® Core™2 Quad processor Q8300, 4 MB, 1333 MHz Intel® Core™2 Duo processor E8600, 6 MB, 1333 MHz Intel® Core™2 Duo processor E8500, 6 MB, 1333 MHz Intel® Core™2 Duo processor E8400, 6 MB, 1333 MHz Intel® Core™2 Duo processor E7600, 3 MB, 1066 MHz Intel® Core™2 Duo processor E7500, 3 MB, 1066 MHz Intel® Pentium® processor E6300, 2 MB, 1066 MHz Intel® Pentium® processor E5500, 2 MB, 1066 MHz Intel® Pentium® processor E5400, 2 MB, 800 MHz Intel® Celeron® processor E3200, 1 MB, 800 MHz
Memory	Up to 16 GB, 4 DIMM (DDR3, 1066 MHz) slot(s) Dual channel support. For dual channel performance, identical memory modules in each channel are necessary (minimum 2 modules).
Serial ATA	4
thereof eSATA	2 (optional)
Controller functions	Serial ATA II, NCQ and 3 GBit, AHCI, Raid 1/0
Drives (optional)	1.44 MB Floppy DVD-ROM, SATA I DVD Super Multi, SATA I Blu-ray Disc Triple Writer, SATA I MultiCard Reader 20in1, 3.5-inch, USB 2.0
Hard disk drive	SATA II, 7200 rpm, 160 GB, 2.5-inch, S.M.A.R.T. SATA II, 7200 rpm, 160 GB, 3.5-inch, S.M.A.R.T. SATA II, 7200 rpm, 250 GB, 3.5-inch, S.M.A.R.T. SATA II, 7200 rpm, 320 GB, 3.5-inch, S.M.A.R.T. SATA II, 7200 rpm, 500 GB, 3.5-inch, S.M.A.R.T. SATA II, 7200 rpm, 500 GB, 3.5-inch, S.M.A.R.T. business critical SATA II, 7200 rpm, 1000 GB, 3.5-inch, S.M.A.R.T. SSD SATA, 128 GB, 2.5-inch
Drive bays	1 x 3.5-inch external bay 1 x 3.5-inch internal bay 1 x 5.25-inch external bay
Slots	1 x PCI-Express 2.0 x16 1 x PCI-Express x4 (mech. x8) 2 x PCI slots
Interfaces	1 x Audio: line-in 1 x Audio: line-out 1 x Front audio: headphone 1 x Front audio: microphone 12 x USB 2.0 total 2 x USB front 6 x USB rear 4 x USB internal 1 x VGA 2 x Serial (9pin, 16 byte FIFO, 16550 compatible) (RS-232) optional Parallel (25pin with EPP and ECP) 1 x Ethernet (RJ-45) optional DVI optional DisplayPort 2 x Mouse / Keyboard (PS/2)
Graphics	Intel® GMA 4500, up to 1759 MB
Audio codec	Realtek ALC663
LAN	10/100/1000 MBit/s Intel® 82567 LM
Dimensions (W x D x H)	340 x 380 x 100 mm
Power efficiency	Power supply efficiency (at 230V; 20% / 50% / 100% load): 86% / 89% / 87%
Special features	0-Watt in off- / hibernating mode, Intel® vPro™ technology, Green PC, ENERGY STAR® 5.0, 89% energy efficient power supply, Blue Angel certified, Switched monitor outlet, Family Concept, Twinload, Embedded Security (TPM)
Standard Warranty Duration	3 years
Service Level*	Bring-In/On-Site Service (depending on country)

ESPRIMO E7936 E-STAR 5.0

	Your desktop without compromises
Operating system preinstalled	Genuine Windows® 7 Home Premium Genuine Windows® 7 Professional TwinLoad Windows® XP Professional (DVD)
Facts Mainboard	D3028 (proprietary)
Chipset	Intel® Q45
Processor Type, Second Level cache, Front side bus	Intel® Core™2 Quad processor Q9650, 12 MB, 1333 MHz Intel® Core™2 Quad processor Q9550, 12 MB, 1333 MHz Intel® Core™2 Quad processor Q9505, 6 MB, 1333 MHz Intel® Core™2 Quad processor Q8300, 4 MB, 1333 MHz Intel® Core™2 Duo processor E8600, 6 MB, 1333 MHz Intel® Core™2 Duo processor E8500, 6 MB, 1333 MHz Intel® Core™2 Duo processor E8400, 6 MB, 1333 MHz Intel® Core™2 Duo processor E7600, 3 MB, 1066 MHz Intel® Core™2 Duo processor E7500, 3 MB, 1066 MHz Intel® Pentium® processor E6300, 2 MB, 1066 MHz Intel® Pentium® processor E5500, 2 MB, 1066 MHz Intel® Pentium® processor E5400, 2 MB, 800 MHz Intel® Celeron® processor E3200, 1 MB, 800 MHz
Memory	Up to 16 GB, 4 DIMM (DDR3, 1066 MHz) slot(s) Dual channel support. For dual channel performance, identical memory modules in each channel are necessary (minimum 2 modules).
Serial ATA	4
thereof eSATA	2 (optional)
Controller functions	Serial ATA II, NCQ and 3 GBit, AHCI, Raid 1/0
Drives (optional)	1.44 MB Floppy DVD-ROM, SATA I DVD Super Multi, SATA I Blu-ray Disc Triple Writer, SATA I MultiCard Reader 20in1, 3.5-inch, USB 2.0
Hard disk drive	SATA II, 7200 rpm, 160 GB, 2.5-inch, S.M.A.R.T. SATA II, 7200 rpm, 160 GB, 3.5-inch, S.M.A.R.T. SATA II, 7200 rpm, 250 GB, 3.5-inch, S.M.A.R.T. SATA II, 7200 rpm, 320 GB, 3.5-inch, S.M.A.R.T. SATA II, 7200 rpm, 500 GB, 3.5-inch, S.M.A.R.T. SATA II, 7200 rpm, 500 GB, 3.5-inch, S.M.A.R.T. business critical SATA II, 7200 rpm, 1000 GB, 3.5-inch, S.M.A.R.T. SSD SATA, 128 GB, 2.5-inch
Drive bays	1 x 3.5-inch external bay 1 x 3.5-inch internal bay 1 x 5.25-inch external bay
Slots	1 x PCI-Express 2.0 x16 1 x PCI-Express x4 (mech. x8) 2 x PCI slots
Interfaces	1 x Audio: line-in 1 x Audio: line-out 1 x Front audio: headphone 1 x Front audio: microphone 12 x USB 2.0 total 2 x USB front 6 x USB rear 4 x USB internal 1 x VGA 2 x Serial (9pin, 16 byte FIFO, 16550 compatible) (RS-232) optional Parallel (25pin with EPP and ECP) 1 x Ethernet (RJ-45) optional DVI optional DisplayPort 2 x Mouse / Keyboard (PS/2)
Graphics	Intel® GMA 4500, up to 1759 MB
Audio codec	Realtek ALC663
LAN	10/100/1000 MBit/s Intel® 82567 LM
Dimensions (W x D x H)	340 x 380 x 100 mm
Power efficiency	Power supply efficiency (at 230V; 20% / 50% / 100% load): 84% / 87% / 85%
Special features	Intel® vPro™ technology, Green PC, ENERGY STAR® 5.0, up to 87% energy efficient power supply, Blue Angel certified, Family Concept, Twinload
Standard Warranty Duration	3 years
Service Level*	Bring-In/On-Site Service (depending on country)

SUPERIOR PCS
ESPRIMO

Windows®. Life without Walls™.
Fujitsu recommends Windows 7.

	ESPRIMO E7936 E85+
	Your desktop without compromises
Operating system preinstalled	Genuine Windows® 7 Home Premium Genuine Windows® 7 Professional TwinLoad Windows® XP Professional (DVD)
Facts Mainboard	D3028 (proprietary)
Chipset	Intel® Q45
Processor Type, Second Level cache, Front side bus	Intel® Core™2 Quad processor Q9650, 12 MB, 1333 MHz Intel® Core™2 Quad processor Q9550, 12 MB, 1333 MHz Intel® Core™2 Quad processor Q9505, 6 MB, 1333 MHz Intel® Core™2 Quad processor Q8300, 4 MB, 1333 MHz Intel® Core™2 Duo processor E8600, 6 MB, 1333 MHz Intel® Core™2 Duo processor E8500, 6 MB, 1333 MHz Intel® Core™2 Duo processor E8400, 6 MB, 1333 MHz Intel® Core™2 Duo processor E7600, 3 MB, 1066 MHz Intel® Core™2 Duo processor E7500, 3 MB, 1066 MHz Intel® Pentium® processor E6300, 2 MB, 1066 MHz Intel® Pentium® processor E5500, 2 MB, 1066 MHz Intel® Pentium® processor E5400, 2 MB, 800 MHz Intel® Celeron® processor E3200, 1 MB, 800 MHz Intel® Celeron® processor 450, 512 KB, 800 MHz
Memory	Up to 16 GB, 4 DIMM (DDR3, 1066 MHz) slot(s) Dual channel support. For dual channel performance, identical memory modules in each channel are necessary (minimum 2 modules).
Serial ATA	4
thereof eSATA	2 (optional)
Controller functions	Serial ATA II, NCQ and 3 GBit, AHCI, Raid 1/0
Drives (optional)	1.44 MB Floppy DVD-ROM, SATA I DVD Super Multi, SATA I Blu-ray Disc Triple Writer, SATA I MultiCard Reader 20in1, 3.5-inch, USB 2.0
Hard disk drive	SATA II, 7200 rpm, 160 GB, 2.5-inch, S.M.A.R.T. SATA II, 7200 rpm, 160 GB, 3.5-inch, S.M.A.R.T. SATA II, 7200 rpm, 250 GB, 3.5-inch, S.M.A.R.T. SATA II, 7200 rpm, 320 GB, 3.5-inch, S.M.A.R.T. SATA II, 7200 rpm, 500 GB, 3.5-inch, S.M.A.R.T. SATA II, 7200 rpm, 500 GB, 3.5-inch, S.M.A.R.T. business critical SATA II, 7200 rpm, 1000 GB, 3.5-inch, S.M.A.R.T. SSD SATA, 128 GB, 2.5-inch
Drive bays	1 x 3.5-inch external bay 1 x 3.5-inch internal bay 1 x 5.25-inch external bay
Slots	1 x PCI-Express 2.0 x16 1 x PCI-Express x4 (mech. x8) 2 x PCI slots
Interfaces	1 x Audio: line-in 1 x Audio: line-out 1 x Front audio: headphone 1 x Front audio: microphone 12 x USB 2.0 total 2 x USB front 6 x USB rear 4 x USB internal 1 x VGA 2 x Serial (9pin, 16 byte FIFO, 16550 compatible) (RS-232) optional Parallel (25pin with EPP and ECP) 1 x Ethernet (RJ-45) optional DVI optional DisplayPort 2 x Mouse / Keyboard (PS/2)
Graphics	Intel® GMA 4500, up to 1759 MB
Audio codec	Realtek ALC663
LAN	10/100/1000 MBit/s Intel® 82567 LM
Dimensions (W x D x H)	340 x 380 x 100 mm
Power efficiency	Power supply efficiency (at 230V; 20% / 50% / 100% load): 84% / 87% / 85%
Special features	Intel® vPro™ technology, Green PC, up to 87% energy efficient power supply, Blue Angel certified, Family Concept, Twinload
Standard Warranty Duration	3 years
Service Level*	Bring-In/On-Site Service (depending on country)

	ESPRIMO Q9000
	The mini with more PC per cm³
Operating system preinstalled	Genuine Windows® 7 Home Premium Genuine Windows® 7 Professional TwinLoad Windows® XP Professional (DVD)
Chipset	Intel® QM57
Processor Type, Second Level cache, Front side bus	Intel® Core™ i5 processor i5-520M Intel® Core™ i3 processor i3-330M
Memory	Up to 4 GB, 2 SO DIMM, 1066 MHz slot(s)
	Dual channel support. For dual channel performance, a minimum of 2 memory modules have to be ordered. Capacity per channel has to be the same , In configurations with 4 GB the visible memory may be reduced to approximately 3.5 GB or less (for 32 bit operating systems, depending on system configuration)
Serial ATA	3
Controller functions	Serial ATA II, 3 GBit, AHCI
Drives (optional)	DVD Super Multi Slot-in slim, SATA Blu-ray Combo SATA Slot-in slim, SATA
Hard disk drive	SATA, 5400 rpm, 160 GB, 2.5-inch SATA, 5400 rpm, 250 GB, 2.5-inch SATA II, 5400 rpm, 320 GB, 2.5-inch SATA II, 5400 rpm, 500 GB, 2.5-inch SATA II, 7200 rpm, 160 GB, 2.5-inch, S.M.A.R.T.
Drive bays	1 x 2.5-inch bay 1 x 5.25-inch external bay
Interfaces	1 x Audio: line-in / microphone 1 x Audio: line-in 1 x (optical) Audio: line-out / headphones / SPDIF - Front audio: line-in / microphone - Front audio: headphone 6 x USB 2.0 total 2 x USB front 4 x USB rear VGA via DVI to VGA-Adapter 1 x Ethernet (RJ-45) 1 x Kensington Lock support 1 x DVI 1 x eSATA 1 x HDMI
Graphics	Intel® HD Graphics
Audio codec	Realtek ALC662
LAN	10/100/1000 MBit/s Intel® 82577 LM
	Optional WLAN, optional Bluetooth
Dimensions (W x D x H)	165 x 168 x 57 mm
Special features	Intel® vPro™ technology, ENERGY STAR® 5.0, Mobile on Desktop, Backpack Solution, Extremely space-saving design, Twinload, less than 2 liters in volume, 1.4 kg light
Standard Warranty Duration	3 years
Service Level*	Bring-In/On-Site Service (depending on country)